

LongLiner

Series 4000



SPECIFICATIONS

Reel Assembly:	
Height Extended Handle	103cm (40.5")
Height Collapsed Handle	57cm (22.5")
Depth	60cm (23.5")
Width	66cm (26")
Width With Handle	81cm (32")
Weight (Reel and Cart Only)	35kg (77lbs)
Plate Size	< 1000m/3500ft - 42cm (16.5"), > 1000m/3500ft - 46cm (18")
Plate Material	Steel, Powder Coated
Brake	Spring Loaded
Handle	Colaspable
Manual Hand Crank Arm	Removable
Tape Guide	NA
Test Points	See Instructions
Tape Lengths	450m/1500ft,600m/2000ft,750m/2500ft,900m/3000ft,1000m/3500ft,1200m/4000ft
Tape:	
Tape	High Tensile Stainless Steel
Jacketing	Polyethylene
Conductors	7 strand (4 S/S & 3 copper)
Markings	Metric or Engineering Scale - Under Jacketing
Width	9.5mm (3/8")
Dog Bone Profile	Yes
Break Strength	127kg (280lbs)
Probe:	
Weight	158g (.35lb)
Length	17.5cm (7")
Diameter	16mm (5/8")
Removable	No
Depth Rating	IP68
Break Strain	68kg (150lbs)
Wetted Material	S/S, Buna, Nylon, ABS & Teflon, Polyurethane
Electronic Panel:	
Operating Mode	Static & drawDown
Power Source	9 Volt Alkaline
Sensitivity Control	S/S & Aluminum
Audio/Visual Indication	Ultra Bright LED & 80dbi Buzzer
Rating	IP65
Removable	Yes
Maximum Temperature	80°C
Electrical Characteristics:	
Motor	12v DC
Power Supply	12v Automotive Grade (ONLY)
Battery Voltage	Displayed on Motor Controller
Speed Control	Wind and Rewind
Warranty:	
	1 Year (Probe 1 Year)

