



HERON
INSTRUMENTS INC.

For Good Measure

dipperLog

Groundwater Data Logging Made Affordable

Heron Instruments' **dipperLogs** are a durable, versatile and cost effective tool which will deliver accurate water level and temperature readings for many years. Groundwater professionals have been successfully employing the **Heron** family of instrumentation to monitor both open waters and wells, to perform pump and slug tests, and to complete wetland and tidal studies with excellent results for over 20 years.

With the dedicated, intuitive software, the **dipperLog** is quick and easy to program and launch and allows for simple data recovery. Easily save your data in a tabular display and graph and view both parameters side by side in a split screen.

Heron also offers various accessories to further enhance your logging experience. The wide range of transducer values (available in both absolute and vented models) will ensure the collection of the most accurate of levels.



dipperLog TOUGH

dipperLog TOUGH is a **premium logger**, with titanium body and transducer coupled with **Teflon O-rings**, is suitable for use in the most caustic and hazardous of environments. The **dipperLog TOUGH** offers a memory capacity of **128,000 data points** and a choice of pressure ranges.



dipperLog 128+

The **dipperLog 128** our flagship logger, offers a maximum storage capacity of **128,000 data points** and an extended battery life up to 15 years. The **dipperLog 128** comes in a wide variety of pressure ranges and deployment options.



dipperLog VENTED*

The **dipperLog VENTED**, incorporates a **gauged transducer** that measures pressure exempt from barometric influences. The **dipperLog VENTED** is **removable from the vent cable** allowing for easy field replacement.



4-20mA Pressure Transmitter*

The **4-20 mA Pressure Transmitter** is easily integrated into an existing **SCADA system** or with a third party data logger. It will provide a continuous water level reading for your application. It can also be equipped with a digital display.



barLog

The **barLog** is configured to **measure barometric pressure fluctuations** necessary to compensate your absolute **dipperLog** data files. The **barLog** takes readings every 1 hour and has a capacity for **128,000 data points**.

◇ *Dependent upon use*
* *Manufactured with wetted materials not known to contain PFAS*

www.heroninstruments.com

Specifications

	dipperLog TOUGH	dipperLog 128	dipperLog VENTED
Performance			
# of Data Points	128,000	128,000	128,000
Download Speed	21,333.33/min	21,333.33/min	21,333.33/min
Accuracy %FS	0.05	0.05	0.05
Stability %FS/Year	0.20	0.20	0.20
Operating Features			
Pressure Ranges	10m/30ft, 30m/100ft, 60m/200ft, 120m/400ft	10m/30ft, 30m/100ft, 60m/200ft, 120m/400ft	10m/30ft, 30m/100ft, 60m/200ft, 120m/400ft
Overpressure Rating	2X	2X	2X
Operating Temperature	-20°C to 80°C	-20°C to 80°C	-20°C to 80°C
Pressure Resolution % FS	0.001	0.001	0.001
Expected Battery Life◇	Up to 15 Years	Up to 15 Years	Up to 15 Years
Warranty	2 Years	2 Years	2 Years
Physical Characteristics			
Wetted Material	Titanium & Delrin®	316 SS & Delrin®	316 SS & Delrin®
O-Rings	Teflon™	Rubber Buna	Rubber Buna
Transducer	Titanium Piezoresistive Silicon	316 SS Piezoresistive Silicon	316 SS Piezoresistive Silicon
Length	130mm	130mm	130mm
Diameter	22mm	22mm	22mm
Weight	105g	160g	160g
Deployment Options All Absolute Deployments Require Compensation	Suspended*, Direct Read*, Reel*, dipperLog SMART*Δ	Suspended*, Direct Read*, Reel*, dipperLog SMART*Δ	Suspended*, Direct Read*, Reel*

*Features Available for Additional Costs
*ΔWireless Monitoring System Compatible

◇ Dependent upon use

Suspended Version

This is the simplest and most inexpensive method of deploying a dipperLog. Suspend the dipperLog in the well using a non-corrosive, no-stretch wire or cord. No communication is possible with the dipperLog in-situ, the dipperLog must be programmed and started before deployment then recovered for data retrieval and reprogramming.



Direct Read Well Head Version

This is the least labour intensive option. The dipperLog is suspended on a direct read cable, which establishes a connection to the dipperLog at the wellhead. Programming of the dipperLog, downloading of data and stopping and starting data collection can be done while the logger is deployed.



Available in both absolute and vented models. Real time display is available with this configuration.

Accessories:

<p>Software & PC Communication Cable</p>  <p>PN# 5009</p>	<p>barLog for Barometric Compensation</p>  <p>PN# 5116</p>	<p>tapNtell Surface Mount Display</p>  <p>PN# 5020</p>	<p>showNtell Hand Held Display</p>  <p>PN# 5018</p>	<p>Digital Display 4-20mA</p>  <p>PN# 5031</p>
---	--	--	---	--



Specifications

4-20mA Pressure Transmitter	barLog	
		Performance
N/A	128,000	# of Data Points
N/A	21,333.33/min	Download Speed
0.05	0.05	Accuracy %FS
0.20	0.20	Stability %FS/Year
		Operating Features
10m/30ft, 30m/100ft, 60m/200ft, 120m/400ft	N/A	Pressure Ranges
2X	2X	Overpressure Rating
-20°C to 80°C	-20°C to 80°C	Operating Temperature
0.001	0.006	Pressure Resolution % FS
N/A	Up to 15 Years	Expected Battery Life◇
2 Years	2 Years	Warranty
		Physical Characteristics
316 SS & Delrin®	316 SS & Delrin®	Wetted Material
Rubber Buna	Rubber Buna	O-Rings
316 SS Piezoresistive Silicon	316 SS Piezoresistive Silicon	Transducer
130mm	105mm	Length
22mm	22mm	Diameter
160g	130g	Weight
N/A	N/A	Deployment Options All Absolute Deployments Require Compensation <i>*Features Available for Additional Costs</i> <i>*◇Wireless Monitoring System Compatible</i>

Reel Version

The reel version is an ideal option when transporting your **dipperLog** from site to site for pump and slug tests or any other short term deployment. Programming and downloading of the data is capable via the connection on the face plate on the reel.

Available in both absolute and vented models. Real time display is available with this configuration.



◇ Dependent upon use

4-20mA

The **4-20mA Pressure Transmitter** is easy to install by simply attaching the vented cable to an existing SCADA system. A two wire 4-20mA current loop is used for signal transmission. This is a pressure sensor only and has no data logging capability.



SCADA systems are not available through Heron Instruments.

SDI-12 Interface Cable



PN# 5021

Well Mounting Kit



PN# 5023

Lockable Well Caps



PN# 5007

Lockable Well Plug



PN# 5006

dipperLog Carry Case



PN# 5054






Selection Guide

Pressure Range	dipperLog TOUGH	dipperLog 128	dipperLog VENTED
B (10m/30ft)	54T-B	54128-B	54VEN-B
C (30m/100ft)	54T-C	54128-C	54VEN-C
D (60m/200ft)	54T-D	54128-D	54VEN-D
E (120m/400ft)	54T-E	54128-E	54VEN-E


Suspended Version *(Remove from Well to Communicate)*

Absolute Logger	Vented Logger
dipperLog (128, TOUGH)	dipperLog VENTED
barLog for Barometric Compensation	Vent Cap Adapter
Stainless Steel Suspension Wire	Stainless Steel Suspension Wire
Kevlar Suspension Cord	Kevlar Suspension Cord
Suspension Crimps	Suspension Crimps
PC Communication Cable	PC Communication Cable
dipperLog Software	dipperLog Software




Direct Read Version *(Communicate While in Well)*

Absolute Logger	Vented Logger
dipperLog (128, TOUGH)	dipperLog VENTED
Direct Read Cable	Vented Direct Read Cable
Direct Read Well Head	Vented Direct Read Well Head
Mounting Bracket	Mounting Bracket
PC Communication Cable	PC Communication Cable
barLog for Barometric Compensation	N/A
dipperLog Software	dipperLog Software



Reel Version *(Portable, Communicate While in Well)*

Absolute Logger	Vented Logger
dipperLog (128, TOUGH)	dipperLog VENTED
Reel	Vented Reel
Direct Read Cable	Vented Direct Read Cable
PC Communication Cable	PC Communication Cable
barLog for Barometric Compensation	N/A
dipperLog Software	dipperLog Software



HERON INSTRUMENTS INC.

447 Moxley Rd. Dundas, ON Canada L9H 5E2 | TF: 800-331-2032 | T: 905-628-4999 | info@heroninstruments.com

Please visit our website www.heroninstruments.com for more information on the complete Heron line.

 Made in Canada